



refrigerated incubators

WWW.FALCINSTRUMENTS.IT

Refrigerated incubators

REFRIGERATED INCUBATORS 0°C ÷ 80°C



LCD touch screen display
External structure in steel sheet coated with antiacid epoxy powder.
Inner chamber in 18/8 stainless steel
Inner door in tempered glass



Digital temperature control via microprocessor PID action with PT 100 probe
Working temperature 0÷80°C



Digital timer hh:mm:ss or infinite



Key lock on the door



Forced ventilation



Setting for 4 languages (Italian-English-French-Spanish)
Program saving function (temperature/maintenance)
Programmable delayed start (day/hour)
Calibration report performed with Accredia-certified LAT reference instrument
N°2 of Ø10mm holes on the upper side for thermometer or control probes insertion

Technical data		ICT-C 100	ICT-C 250
Capacity	lt	100	250
Temperature	°C	0-80°C	0-80°C
Display resolution	°C	0.1	0.1
Timer	hh:mm:ss	99:59:59 or infinite	99:59:59 or infinite
Temperature accuracy	4°C	+/-0.4	+/-0.4
	22°C	+/-0.4	+/-0.4
	37°C	+/-0.4	+/-0.4
	60°C	+/-0.8	+/-0.8
	80°V	+/-0.8	+/-0.8
Number racks included	N°	2	2
Maximum number racks	N°	4	6
Gas		R290	R290
Maximum capacity for shelves	Kg	15	15
Max item weight	Kg	60	90
Internal dimension LxPxH	mm	521x535x575	521x535x1058
External dimension LxPxH	mm	621x685x1125	621x685x1608
Power	W	1200	1200
Weight	Kg	82	104
Code		720.2070.90	720.2070.91

V/HZ 220/240-50/60

SAFETY CLASS 0

PROTECTION CLASS IP 42

ACCESSORI:

720.2091.47 Gridded shelf for refrigerated incubator ICT- C 100 lt

720.2091.48 Gridded shelf for refrigerated incubator ICT- C 250 lt

720.2091.49 Perforated shelf for refrigerated incubator ICT- C 100 lt

720.2091.50 Perforated shelf for refrigerated incubator ICT- C 250 lt

Refrigerated incubators with ramps

REFRIGERATED INCUBATORS 0°C ÷ 80°C



LCD touch screen display
External structure in steel sheet coated with antiacid epoxy powder.
Inner chamber in 18/8 stainless steel
Inner door in tempered glass



Digital temperature control via microprocessor PID action with PT 100 probe
Working temperature 0÷80°C



Digital timer hh:mm:ss or infinite



Key lock on the door



Forced ventilation



Setting for 4 languages (Italian-English-French-Spanish)
Programmable with 20 ramps setting 8 temperatures and lengths of time
Calibration report performed with Accredia-certified LAT reference instrument
N°2 of Ø10mm holes on the upper side for thermometer or control probes insertion



Technical data		ICT-CR 100	ICT-CR 250
Capacity	lt	100	250
Temperature	°C	0-80°C	0-80°C
Display resolution	°C	0.1	0.1
Timer	hh:mm:ss	99:59:59 or infinite	99:59:59 or infinite
Temperature accuracy	4°C	+/-0.4	+/-0.4
	22°C	+/-0.4	+/-0.4
	37°C	+/-0.4	+/-0.4
	60°C	+/-0.8	+/-0.8
	80°C	+/-0.8	+/-0.8
Number racks included	N°	2	2
Maximum number racks	N°	4	6
Gas		R290	R290
Maximum capacity for shelves	Kg	15	15
Max item weight	Kg	60	90
Internal dimension LxPxH	mm	521x535x575	521x535x1058
External dimension LxPxH	mm	621x685x1125	621x685x1608
Power	W	1200	1200
Weight	Kg	82	104
Code		720.2070.92	720.2070.93

V/HZ 220/240-50/60

SAFETY CLASS 0

PROTECTION CLASS IP 42

ACCESSORI:

720.1091.10 Wifi module remote monitoring via APP

720.2091.47 Gridded shelf for refrigerated incubator ICT-C AR 100 lt

720.2091.48 Gridded shelf for refrigerated incubator ICT-C AR 250 lt

720.2091.49 Perforated shelf for refrigerated incubator ICT-C AR 100 lt

720.2091.50 Perforated shelf for refrigerated incubator ICT-C AR 250 lt



FALC INSTRUMENTS s.r.l.

Via G. M. Compagnoni, 2
24047 Treviglio (BG) - Italy
+39 0363 304660 | falc@falcinstruments.it

WWW.FALCINSTRUMENTS.IT